

# MATERIAL SAFETY DATA SHEET

Total Solutions  
P.O. Box 240014  
Milwaukee, WI 53224



GENERAL INFORMATION NUMBER: (414) 354-6417  
CHEMTREC: (800) 424-9300

REVISION DATE: September 8, 2003  
DATE OF ISSUE: September 8, 2003

## I - Product Identification

### dB Solvent-CS

PRODUCT CODE: 0394

CHEMICAL FORMULATION: Solvent based degreaser

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0  
HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

## II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX %	OSHA PEL	ACGIH TLV	EPA 40 CFR:			CAS #
				302	355	372	
Mineral Spirits	75.0-85.0	N/E	100 ppm	N	N	N	8052-41-3
d-Limonene	15.0-25.0	N/E	N/E	Y	N	N	5989-27-5

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit  
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No  
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).  
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).  
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

## III - Physical Data

BOILING POINT (°F): N/D SPECIFIC GRAVITY (WATER = 1): 0.803  
VAPOR PRESSURE (mm Hg): N/D VOC CONTENT (% by weight): > 90.0  
VAPOR DENSITY (AIR = 1): N/D EVAPORATION RATE (WATER = 1): > 1.0  
SOLUBILITY IN WATER: Insoluble pH: N/A  
APPEARANCE AND ODOR: Clear, colorless liquid; solvent odor

## IV - Fire and Explosion Hazard Data

FLASH POINT (°F): 115 (TEST METHOD): Closed cup  
FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: N/D LOWER: N/D  
EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.  
SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.  
UNUSUAL FIRE AND EXPLOSION HAZARD: Use water spray to cool fire-exposed containers. Solvent vapors may cause flashback. Vapors are heavier than air and may travel along the ground or be moved by ventilation.

---

**V - Reactivity Data**

---

**STABILITY:** Stable

**INCOMPATIBILITY:** Strong oxidizing agents.

**CONDITIONS TO AVOID:** Heat or open flame.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may yield thick smoke, irritating fumes and oxides of carbon.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** None

---

**VI - Health Hazard Data**

---

**ROUTES OF ENTRY**      **INHALATION:** X      **EYE CONTACT:** X      **SKIN CONTACT:** X      **INGESTION:** X

**INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS:** None.

**EFFECTS OF OVEREXPOSURE**

**IF IN EYES:** Severe irritation, and redness, tearing, blurred vision.

**IF ON SKIN:** Irritation, chapping and dermatitis, with prolonged or repeated exposure. Contains a possible sensitizer.

**IF SWALLOWED:** Nausea, cramps, diarrhea. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

**IF INHALED:** Irritation to respiratory tract, dizziness, weakness, headache, nausea, and unconsciousness.

**EMERGENCY AND FIRST AID PROCEDURES**

**IF IN EYES:** Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

**IF ON SKIN:** Remove contaminated clothing and launder separately before re-use. Wash with soap and water. If irritation persists, obtain medical attention.

**IF SWALLOWED:** Call a physician or poison control center immediately. Do not induce vomiting. Rinse mouth with water, then drink one glass of water. Never give anything by mouth to an unconscious person.

**IF INHALED:** Remove person to fresh air. If irritation persists, obtain medical attention.

---

**VII - Spill or Leak Protection**

---

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Ventilate area and extinguish all sources of ignition. Contain spill. Soak up with inert absorbent and place in a properly labeled closed container for disposal.

**WASTE DISPOSAL METHOD:** Consult local environmental authorities.

---

**VIII - Special Protection Information**

---

**RESPIRATORY PROTECTION:** Use with adequate ventilation. Do not breathe vapors or mists. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

**VENTILATION**

**LOCAL:** Recommended

**MECHANICAL:** Not required

**PROTECTIVE GLOVES:** Chemical resistant.

**EYE PROTECTION:** Chemical goggles or safety glasses.

**OTHER PROTECTIVE EQUIPMENT:** Protective clothing, eye wash station.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store in a cool, dry place, away from heat or open flame Wash thoroughly after handling. Keep container tightly closed when not in use.

**OTHER PRECAUTIONS:** Keep out of reach of children. Do not cut or weld on empty container as they may contain combustible residues.

---

**IX - Transportation Information (ground transportation only)**

---

**DOT PROPER SHIPPING NAME:** None

**DOT CLASS:** None

**DOT ID NUMBER:** None

**DOT PACKING GROUP:** None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

---

**REVISION DATE:** September 8, 2003

**Prepared by:** PMR

**DATE OF ISSUE:** September 8, 2003

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Total Solutions assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.